




Electric four wheel counterbalance forklift truck


EFG MC 316k / 316 / 320

Lift height: 3000-6500 mm / Load capacity: 1600-2000 kg

EFG MC 316k / 316 / 320



EFG MC 316k / 316 / 320



EFG MC 316k / 316 / 320

EFG MC 316k, EFG MC 316	Lift (h3)	Retracted mast height (h1)	Free lift (h2)	Extended mast height (h4)	Forward/backward tilt of mast
Duplex mast ZT	3000 mm	2000 mm	150 mm	3555 mm	7 / 5 °
	3300 mm	2150 mm	150 mm	3855 mm	7 / 5 °
	3600 mm	2300 mm	150 mm	4155 mm	7 / 5 °
	4000 mm	2500 mm	150 mm	4555 mm	7 / 5 °
	4500 mm	2800 mm	150 mm	5055 mm	7 / 5 °
	5000 mm	3050 mm	150 mm	5555 mm	7 / 5 °
Duplex mast ZZ	3300 mm	2105 mm	1545 mm	3855 mm	7 / 5 °
	3600 mm	2255 mm	1695 mm	4155 mm	7 / 5 °
	4000 mm	2455 mm	1895 mm	4555 mm	7 / 5 °
Triplex mast DZ	4500 mm	2005 mm	1445 mm	5055 mm	7 / 5 °
	4800 mm	2105 mm	1545 mm	5355 mm	7 / 5 °
	5000 mm	2180 mm	1620 mm	5555 mm	7 / 5 °
	5500 mm	2355 mm	1795 mm	6055 mm	7 / 5 °
	6000 mm	2555 mm	1995 mm	6555 mm	7 / 5 °
	6500 mm	2805 mm	2245 mm	7055 mm	7 / 5 °
EFG MC 320	Lift (h3)	Retracted mast height (h1)	Free lift (h2)	Extended mast height (h4)	Forward/backward tilt of mast
Duplex mast ZT	3000 mm	2000 mm	150 mm	3555 mm	7 / 5 °
	3300 mm	2150 mm	150 mm	3855 mm	7 / 5 °
	3600 mm	2300 mm	150 mm	4155 mm	7 / 5 °
	4000 mm	2500 mm	150 mm	4555 mm	7 / 5 °
	4500 mm	2800 mm	150 mm	5055 mm	7 / 5 °
	5000 mm	3050 mm	150 mm	5555 mm	7 / 5 °
Duplex mast ZZ	3300 mm	2105 mm	1488 mm	3855 mm	7 / 5 °
	3600 mm	2255 mm	1638 mm	4155 mm	7 / 5 °
	4000 mm	2455 mm	1838 mm	4555 mm	7 / 5 °
Triplex mast DZ	4500 mm	2005 mm	1388 mm	5055 mm	7 / 5 °
	4800 mm	2105 mm	1488 mm	5355 mm	7 / 5 °
	5000 mm	2180 mm	1563 mm	5555 mm	7 / 5 °
	5500 mm	2355 mm	1738 mm	6055 mm	7 / 5 °
	6000 mm	2555 mm	1938 mm	6555 mm	7 / 5 °
	6500 mm	2805 mm	2188 mm	7055 mm	7 / 5 °

VDI table

Stand-on: 10/2020

Characteristic	1.1	Manufacturer (abbreviated description)			Jungheinrich		
	1.2	Manufacturer's type designation			EFG MC 316K	EFG MC 316	EFG MC 320
	1.3	Drive			Electric		
	1.4	Operation			Seat		
	1.5	Load capacity/load	Q	kg	1600		2000
	1.6	Load centre distance	c	mm	500		
	1.8	Load distance, centre of drive axle to fork	x	mm	352		
	1.9	Wheelbase	y	mm	1398	1506	
Weights	2.1.1	Service weight (incl. battery)		kg	3261	3437	3768
	2.2	Axle load laden front/rear		kg	4094 / 767	3989 / 1048	4971 / 797
	2.3	Axle load unladen front/rear		kg	1596 / 1665	1699 / 1738	1880 / 1888
Wheels/suspension system	3.1	Tyres			SE		
	3.2	Tyre size, front			18x7-8		200/50-10
	3.3	Tyre size, rear			16x6-8		
	3.5	Wheels, number front/back (x=driven)			2x/2		
	3.6	Tread width, front	b ₁₀	mm	904	924	
	3.7	Tread width, rear	b ₁₁	mm	870		
Basic dimensions	4.2	Retracted mast height (h1)	h ₁	mm	2000		
	4.3	Free lift (h2)	h ₂	mm	150		
	4.4	Lift (h3)	h ₃	mm	3000		
	4.5	Extended mast height (h4)	h ₄	mm	3555		
	4.7	Height of overhead guard (cab)	h ₆	mm	2080		
	4.8	Seat height/stand height	h ₇	mm	1030		
	4.12	Coupling height	h ₁₀	mm	475		
	4.12.1	2. Coupling height		mm	0		
	4.19	Overall length	l ₁	mm	2988	3096	
	4.20	Length including fork shank	l ₂	mm	1988	2096	
	4.21.1	Overall width	b ₁	mm	1060		1120
	4.22	Fork dimensions	s/e/l	mm	40 / 100 / 1000		
	4.23	Fork carriage connection class			2A		
	4.24	Fork carriage width	b ₃	mm	980		
	4.31	Ground clearance laden under mast	m ₁	mm	97		
	4.32	Ground clearance centre of wheelbase	m ₂	mm	83		
	4.34	Aisle width (pallet 1000x1200 sideways)	Ast	mm	3404	3485	
	4.34.1	Aisle width (pallet 800x1200 length)	Ast	mm	3569	3656	
	4.35	Turning radius	W _a	mm	1830	1925	
	4.36	Smallest pivot point distance	b ₁₃	mm	498	562	
Performance data	5.1	Travel speed laden/unladen		km/h	16 / 16		
	5.2	Lift speed laden/unladen		m/s	0.43 / 0.66		0.38 / 0.52
	5.3	Lowering speed laden/unladen		m/s	0.55 / 0.55		
	5.5	Drawbar pull laden/unladen		N	2100 / 2450		1900 / 2300
	5.6	Max. drawbar pull laden/unladen		N	13500 / 13500		
	5.7	Gradeability laden/unladen		%	12 / 20		
	5.8	Max. gradeability laden/unladen		%	24 / 35		22 / 35
	5.9	Acceleration time laden/unladen		s	4 / 3.8	4.3 / 4	4.5 / 4
	5.10	Service brake			Mechanical		

E-motor/Electronics	6.1	Drive motor, performance S2 60 min	kW	4.6	
	6.1.1	2. Drive motor, performance S2 60 min	kW	4.6	
	6.2	Lift motor, performance with S3	kW	15.5	
	6.3	Battery according to DIN 43531/35/36		DIN 43531 A	
	6.4	Battery voltage/nominal capacity	V / Ah	48 / 625	48 / 750
	6.5	Battery weight	kg	856	1013
	6.6	Energy consumption according to VDI cycle	kWh/h	4.3	4.8
	6.6.1	Energy consumption according to EN cycle	kWh/h	4.3	4.8
	6.6.2	CO2 equivalent as per EN 16796	kg/h	2.3	2.6
	6.7	Throughput	t/h	118	138
6.8.1	Energy consumption with max. throughput	kWh/h	6.2	6.6	
Other	8.1	Type of drive control		Impulse/AC	
	10.1	Operating pressure for attachment	bar	200	
	10.2	Oil flow for attachments	l/min	25	
	10.7	Sound level as per EN12053, operator's ear	dB (A)	72	
	10.8	Trailer coupling, model/type DIN		DIN 15170 H	
- This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values.					

The German production facilities in
Norderstedt, Moosburg and Landsberg
are certified.

ISO 9001
ISO 14001

Jungheinrich fork lift trucks meet
European safety requirements.



 **JUNGHEINRICH**